


Absolyte – 1-100G39 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP021800 **H** A0FA
 UL 94 V0 NAGP021800 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G39	2	1800	506	217	670	149	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP021800HA0FA	1.94	999999	999999	546	405	321	264	225	165	141
NAGP021800HA0FA	1.92	999999	999999	618	444	348	288	243	177	150
NAGP021800HA0FA	1.90	999999	999999	684	483	378	309	261	189	162
NAGP021800HA0FA	1.88	999999	999999	738	516	399	327	276	201	168
NAGP021800HA0FA	1.86	999999	999999	795	543	423	345	294	210	177
NAGP021800HA0FA	1.84	999999	999999	837	573	444	357	300	216	180
NAGP021800HA0FA	1.83	999999	999999	858	585	453	363	306	216	183
NAGP021800HA0FA	1.81	1434	1191	894	603	465	369	312	219	183
NAGP021800HA0FA	1.80	1476	1218	903	603	468	372	315	219	186
NAGP021800HA0FA	1.78	1566	1263	918	621	471	378	318	219	186
NAGP021800HA0FA	1.75	1677	1338	936	636	474	384	321	225	186