


Absolyte – 1-100G45 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP022088 **H** A0FA

UL 94 V0 NAGP022088 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G45	2	2088	563	218	670	170	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP022088HA0FA	1.94	999999	999999	639	474	375	309	264	195	165
NAGP022088HA0FA	1.92	999999	999999	720	516	408	336	285	207	177
NAGP022088HA0FA	1.90	999999	999999	798	564	441	360	306	222	189
NAGP022088HA0FA	1.88	999999	999999	861	600	468	381	321	234	198
NAGP022088HA0FA	1.86	999999	999999	927	636	492	405	345	243	207
NAGP022088HA0FA	1.84	999999	999999	975	669	519	417	351	252	210
NAGP022088HA0FA	1.83	999999	999999	1002	681	528	423	357	252	213
NAGP022088HA0FA	1.81	1671	1389	1044	705	543	432	366	255	216
NAGP022088HA0FA	1.80	1722	1422	1053	705	546	435	369	255	216
NAGP022088HA0FA	1.78	1827	1476	1071	723	549	441	369	258	216
NAGP022088HA0FA	1.75	1956	1560	1092	744	552	447	375	261	219