


Absolyte – 1-100G51 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP022400 **H** A0FA
 UL 94 V0 NAGP022400 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G51	2	2400	622	218	670	192	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP022400HA0FA	1.94	999999	999999	729	543	429	354	300	222	189
NAGP022400HA0FA	1.92	999999	999999	825	591	465	384	324	237	201
NAGP022400HA0FA	1.90	999999	999999	912	645	504	414	348	255	216
NAGP022400HA0FA	1.88	999999	999999	984	687	534	435	369	267	225
NAGP022400HA0FA	1.86	999999	999999	1059	726	564	462	393	279	237
NAGP022400HA0FA	1.84	999999	999999	1116	765	594	477	402	288	243
NAGP022400HA0FA	1.83	999999	999999	1146	780	603	483	408	288	243
NAGP022400HA0FA	1.81	1911	1587	1194	804	621	492	417	291	246
NAGP022400HA0FA	1.80	1968	1626	1203	807	624	495	420	291	246
NAGP022400HA0FA	1.78	2088	1686	1224	828	627	504	423	294	249
NAGP022400HA0FA	1.75	2235	1785	1248	849	633	510	429	300	249