


Absolyte – 1-100G57 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard	NAGP022688	H	A0FA
UL 94 V0	NAGP022688	V	A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G57	2	2688	679	218	670	213	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP022688HA0FA	1.94	999999	999999	822	609	483	399	339	249	213
NAGP022688HA0FA	1.92	999999	999999	927	666	522	432	366	267	228
NAGP022688HA0FA	1.90	999999	999999	1026	726	567	465	393	285	243
NAGP022688HA0FA	1.88	999999	999999	1107	774	600	489	414	300	255
NAGP022688HA0FA	1.86	999999	999999	1191	816	636	519	444	315	267
NAGP022688HA0FA	1.84	999999	999999	1254	861	666	537	453	324	273
NAGP022688HA0FA	1.83	999999	999999	1290	879	681	543	459	324	273
NAGP022688HA0FA	1.81	2151	1785	1341	906	699	555	471	327	276
NAGP022688HA0FA	1.80	2214	1830	1353	906	702	558	474	330	279
NAGP022688HA0FA	1.78	2349	1896	1377	930	708	567	477	330	279
NAGP022688HA0FA	1.75	2514	2007	1404	957	711	576	483	336	282