


# Absolyte – 1-100G63 data sheet



Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard                      NAGP023000 **H** A0FA

UL 94 V0                      NAGP023000 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G63	2	3000	737	218	670	234	F-M6

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP023000HA0FA	1.94	999999	999999	912	678	537	444	378	276	237
NAGP023000HA0FA	1.92	999999	999999	1032	741	582	480	408	297	252
NAGP023000HA0FA	1.90	999999	999999	1140	807	633	516	438	318	270
NAGP023000HA0FA	1.88	999999	999999	1230	861	669	546	462	336	282
NAGP023000HA0FA	1.88	999999	999999	1230	861	669	546	462	336	282
NAGP023000HA0FA	1.86	999999	999999	1326	909	705	579	492	351	297
NAGP023000HA0FA	1.84	999999	999999	1395	957	741	597	501	360	303
NAGP023000HA0FA	1.83	999999	999999	1434	975	756	606	510	360	306
NAGP023000HA0FA	1.81	2391	1986	1491	1005	777	615	522	363	309
NAGP023000HA0FA	1.80	2460	2034	1506	1008	780	621	525	366	309
NAGP023000HA0FA	1.78	2613	2109	1533	1035	786	630	528	366	309
NAGP023000HA0FA	1.75	2796	2232	1560	1062	792	639	537	375	312