


# Absolyte – 1-100G69 data sheet

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

*Example*

Standard                    NAGP023288 **H** A0FA  
 UL 94 V0                    NAGP023288 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G69	2	3288	794	218	670	255	F-M6

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP023288HA0FA	1.94	999999	999999	1002	744	591	489	414	306	261
NAGP023288HA0FA	1.92	999999	999999	1134	813	639	528	447	327	279
NAGP023288HA0FA	1.90	999999	999999	1254	885	696	570	480	351	297
NAGP023288HA0FA	1.88	999999	999999	1353	945	735	600	507	369	312
NAGP023288HA0FA	1.86	999999	999999	1458	999	777	636	543	384	324
NAGP023288HA0FA	1.84	999999	999999	1533	1050	816	657	552	396	333
NAGP023288HA0FA	1.83	999999	999999	1575	1074	831	666	561	396	336
NAGP023288HA0FA	1.81	2628	2184	1641	1107	855	678	573	402	339
NAGP023288HA0FA	1.80	2706	2235	1656	1107	858	684	579	402	339
NAGP023288HA0FA	1.78	2874	2319	1686	1137	864	693	582	405	342
NAGP023288HA0FA	1.75	3075	2454	1716	1170	870	702	591	411	345