


Absolyte – 1-100G75 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard	NAGP023600	H	A0FA
UL 94 V0	NAGP023600	V	A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G75	2	3600	851	218	670	276	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP023600HA0FA	1.94	999999	999999	1095	813	645	531	453	333	285
NAGP023600HA0FA	1.92	999999	999999	1236	888	699	576	489	357	303
NAGP023600HA0FA	1.90	999999	999999	1368	966	759	621	525	381	324
NAGP023600HA0FA	1.88	999999	999999	1476	1032	801	654	552	402	339
NAGP023600HA0FA	1.86	999999	999999	1590	1089	846	693	591	420	354
NAGP023600HA0FA	1.84	999999	999999	1674	1146	891	717	603	432	363
NAGP023600HA0FA	1.83	999999	999999	1719	1170	906	726	612	432	366
NAGP023600HA0FA	1.81	2868	2382	1791	1206	933	738	627	438	369
NAGP023600HA0FA	1.80	2952	2439	1806	1209	936	744	633	438	372
NAGP023600HA0FA	1.78	3135	2529	1839	1242	942	756	636	441	372
NAGP023600HA0FA	1.75	3354	2676	1872	1275	948	768	645	450	375