


Absolyte – 1-100G81 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP023888 **H** A0FA

UL 94 V0 NAGP023888 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G81	2	3888	908	218	670	296	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP023888HA0FA	1.94	999999	999999	1185	882	699	576	492	360	309
NAGP023888HA0FA	1.92	999999	999999	1341	963	756	624	531	387	330
NAGP023888HA0FA	1.90	999999	999999	1482	1047	822	672	567	414	351
NAGP023888HA0FA	1.88	999999	999999	1599	1119	870	708	600	435	369
NAGP023888HA0FA	1.86	999999	999999	1722	1182	918	753	639	456	384
NAGP023888HA0FA	1.84	999999	999999	1812	1242	966	777	654	468	393
NAGP023888HA0FA	1.83	999999	999999	1863	1269	984	786	663	468	396
NAGP023888HA0FA	1.81	3108	2580	1938	1308	1011	801	678	474	402
NAGP023888HA0FA	1.80	3198	2643	1956	1311	1014	807	684	477	402
NAGP023888HA0FA	1.78	3396	2739	1992	1347	1023	819	687	477	402
NAGP023888HA0FA	1.75	3633	2901	2028	1383	1029	831	699	486	405