


Absolyte – 1-100G93 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP024488 **H** A0FA

UL 94 V0 NAGP024488 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G93	2	4488	1022	218	670	340	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP024488HA0FA	1.94	999999	999999	1368	1017	807	666	567	417	354
NAGP024488HA0FA	1.92	999999	999999	1548	1110	873	720	612	447	381
NAGP024488HA0FA	1.90	999999	999999	1710	1209	948	777	657	477	405
NAGP024488HA0FA	1.88	999999	999999	1845	1290	1002	819	693	504	426
NAGP024488HA0FA	1.86	999999	999999	1989	1362	1059	867	738	525	444
NAGP024488HA0FA	1.84	999999	999999	2091	1434	1113	897	753	540	456
NAGP024488HA0FA	1.83	999999	999999	2151	1464	1134	909	765	540	459
NAGP024488HA0FA	1.81	3585	2979	2238	1509	1167	924	783	546	462
NAGP024488HA0FA	1.80	3690	3051	2259	1512	1170	933	789	549	465
NAGP024488HA0FA	1.78	3918	3162	2298	1554	1179	945	795	552	465
NAGP024488HA0FA	1.75	4194	3348	2340	1596	1188	960	807	561	468