


Absolyte – 1-100G99 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP024800 **H** A0FA

UL 94 V0 NAGP024800 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
1-100G99	2	4800	1080	218	670	361	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP024800HA0FA	1.94	999999	999999	1461	1086	861	711	603	444	378
NAGP024800HA0FA	1.92	999999	999999	1650	1185	933	768	651	477	405
NAGP024800HA0FA	1.90	999999	999999	1824	1290	1011	828	699	510	432
NAGP024800HA0FA	1.88	999999	999999	1968	1377	1071	873	738	537	453
NAGP024800HA0FA	1.86	999999	999999	2121	1452	1131	927	789	561	474
NAGP024800HA0FA	1.84	999999	999999	2232	1530	1188	957	804	576	486
NAGP024800HA0FA	1.83	999999	999999	2292	1560	1209	969	816	576	489
NAGP024800HA0FA	1.81	3825	3177	2388	1611	1245	987	837	585	492
NAGP024800HA0FA	1.80	3936	3252	2409	1614	1248	993	843	585	495
NAGP024800HA0FA	1.78	4179	3372	2451	1656	1257	1008	846	588	498
NAGP024800HA0FA	1.75	4473	3570	2496	1701	1266	1023	861	600	501