


Absolyte – 3-100G13 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP060600 **H** A0FA
 UL 94 V0 NAGP060600 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G13	6	600	506	217	670	149	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP060600HA0FA	1.94	999999	999999	182	135	107	88.0	75.0	55.0	47.0
NAGP060600HA0FA	1.92	999999	999999	206	148	116	96.0	81.0	59.0	50.0
NAGP060600HA0FA	1.90	999999	999999	228	161	126	103	87.0	63.0	54.0
NAGP060600HA0FA	1.88	999999	999999	246	172	133	109	92.0	67.0	56.0
NAGP060600HA0FA	1.86	999999	999999	265	181	141	115	98.0	70.0	59.0
NAGP060600HA0FA	1.84	999999	999999	279	191	148	119	100	72.0	60.0
NAGP060600HA0FA	1.83	999999	999999	286	195	151	121	102	72.0	61.0
NAGP060600HA0FA	1.81	478	397	298	201	155	123	104	73.0	61.0
NAGP060600HA0FA	1.80	492	406	301	201	156	124	105	73.0	62.0
NAGP060600HA0FA	1.78	522	421	306	207	157	126	106	73.0	62.0
NAGP060600HA0FA	1.75	559	446	312	212	158	128	107	75.0	62.0