


Absolyte – 3-100G15 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP060696 **H** A0FA

UL 94 V0 NAGP060696 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G15	6	696	563	218	670	170	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP060696HA0FA	1.94	999999	999999	213	158	125	103	88.0	65.0	55.0
NAGP060696HA0FA	1.92	999999	999999	240	172	136	112	95.0	69.0	59.0
NAGP060696HA0FA	1.90	999999	999999	266	188	147	120	102	74.0	63.0
NAGP060696HA0FA	1.88	999999	999999	287	200	156	127	107	78.0	66.0
NAGP060696HA0FA	1.86	999999	999999	309	212	164	135	115	81.0	69.0
NAGP060696HA0FA	1.84	999999	999999	325	223	173	139	117	84.0	70.0
NAGP060696HA0FA	1.83	999999	999999	334	227	176	141	119	84.0	71.0
NAGP060696HA0FA	1.81	557	463	348	235	181	144	122	85.0	72.0
NAGP060696HA0FA	1.80	574	474	351	235	182	145	123	85.0	72.0
NAGP060696HA0FA	1.78	609	492	357	241	183	147	123	86.0	72.0
NAGP060696HA0FA	1.75	652	520	364	248	184	149	125	87.0	73.0