


Absolyte – 3-100G19 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP060896 **H** A0FA
 UL 94 V0 NAGP060896 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G19	6	896	679	218	670	213	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP060896HA0FA	1.94	999999	999999	274	203	161	133	113	83.0	71.0
NAGP060896HA0FA	1.92	999999	999999	309	222	174	144	122	89.0	76.0
NAGP060896HA0FA	1.90	999999	999999	342	242	189	155	131	95.0	81.0
NAGP060896HA0FA	1.88	999999	999999	369	258	200	163	138	100	85.0
NAGP060896HA0FA	1.86	999999	999999	397	272	212	173	148	105	89.0
NAGP060896HA0FA	1.84	999999	999999	418	287	222	179	151	108	91.0
NAGP060896HA0FA	1.83	999999	999999	430	293	227	181	153	108	91.0
NAGP060896HA0FA	1.81	717	595	447	302	233	185	157	109	92.0
NAGP060896HA0FA	1.80	738	610	451	302	234	186	158	110	93.0
NAGP060896HA0FA	1.78	783	632	459	310	236	189	159	110	93.0
NAGP060896HA0FA	1.75	838	669	468	319	237	192	161	112	94.0