


# Absolyte – 3-100G21 data sheet



Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

*Example*

Standard                    NAGP061000 **H** A0FA  
 UL 94 V0                    NAGP061000 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G21	6	1000	737	218	670	234	F-M6

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061000HA0FA	1.94	999999	999999	304	226	179	148	126	92.0	79.0
NAGP061000HA0FA	1.92	999999	999999	344	247	194	160	136	99.0	84.0
NAGP061000HA0FA	1.90	999999	999999	380	269	211	172	146	106	90.0
NAGP061000HA0FA	1.88	999999	999999	410	287	223	182	154	112	94.0
NAGP061000HA0FA	1.86	999999	999999	442	303	235	193	164	117	99.0
NAGP061000HA0FA	1.84	999999	999999	465	319	247	199	167	120	101
NAGP061000HA0FA	1.83	999999	999999	478	325	252	202	170	120	102
NAGP061000HA0FA	1.81	797	662	497	335	259	205	174	121	103
NAGP061000HA0FA	1.80	820	678	502	336	260	207	175	122	103
NAGP061000HA0FA	1.78	871	703	511	345	262	210	176	122	103
NAGP061000HA0FA	1.75	932	744	520	354	264	213	179	125	104