


Absolyte – 3-100G23 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP061096 **H** A0FA

UL 94 V0 NAGP061096 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G23	6	1096	794	218	670	255	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061096HA0FA	1.94	999999	999999	334	248	197	163	138	102	87.0
NAGP061096HA0FA	1.92	999999	999999	378	271	213	176	149	109	93.0
NAGP061096HA0FA	1.90	999999	999999	418	295	232	190	160	117	99.0
NAGP061096HA0FA	1.88	999999	999999	451	315	245	200	169	123	104
NAGP061096HA0FA	1.86	999999	999999	486	333	259	212	181	128	108
NAGP061096HA0FA	1.84	999999	999999	511	350	272	219	184	132	111
NAGP061096HA0FA	1.83	999999	999999	525	358	277	222	187	132	112
NAGP061096HA0FA	1.81	876	728	547	369	285	226	191	134	113
NAGP061096HA0FA	1.80	902	745	552	369	286	228	193	134	113
NAGP061096HA0FA	1.78	958	773	562	379	288	231	194	135	114
NAGP061096HA0FA	1.75	1025	818	572	390	290	234	197	137	115