


Absolyte – 3-100G25 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP061200 **H** A0FA
 UL 94 V0 NAGP061200 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G25	6	1200	851	218	670	276	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061200HA0FA	1.94	999999	999999	365	271	215	177	151	111	95.0
NAGP061200HA0FA	1.92	999999	999999	412	296	233	192	163	119	101
NAGP061200HA0FA	1.90	999999	999999	456	322	253	207	175	127	108
NAGP061200HA0FA	1.88	999999	999999	492	344	267	218	184	134	113
NAGP061200HA0FA	1.86	999999	999999	530	363	282	231	197	140	118
NAGP061200HA0FA	1.84	999999	999999	558	382	297	239	201	144	121
NAGP061200HA0FA	1.83	999999	999999	573	390	302	242	204	144	122
NAGP061200HA0FA	1.81	956	794	597	402	311	246	209	146	123
NAGP061200HA0FA	1.80	984	813	602	403	312	248	211	146	124
NAGP061200HA0FA	1.78	1045	843	613	414	314	252	212	147	124
NAGP061200HA0FA	1.75	1118	892	624	425	316	256	215	150	125