


# Absolyte – 3-100G27 data sheet

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

*Example*

Standard                    NAGP061296 **H** A0FA  
 UL 94 V0                    NAGP061296 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G27	6	1296	908	218	670	296	F-M6

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061296HA0FA	1.94	999999	999999	395	294	233	192	164	120	103
NAGP061296HA0FA	1.92	999999	999999	447	321	252	208	177	129	110
NAGP061296HA0FA	1.90	999999	999999	494	349	274	224	189	138	117
NAGP061296HA0FA	1.88	999999	999999	533	373	290	236	200	145	123
NAGP061296HA0FA	1.86	999999	999999	574	394	306	251	213	152	128
NAGP061296HA0FA	1.84	999999	999999	604	414	322	259	218	156	131
NAGP061296HA0FA	1.83	999999	999999	621	423	328	262	221	156	132
NAGP061296HA0FA	1.81	1036	860	646	436	337	267	226	158	134
NAGP061296HA0FA	1.80	1066	881	652	437	338	269	228	159	134
NAGP061296HA0FA	1.78	1132	913	664	449	341	273	229	159	134
NAGP061296HA0FA	1.75	1211	967	676	461	343	277	233	162	135