


Absolyte – 3-100G29 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP061400 **H** A0FA
 UL 94 V0 NAGP061400 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G29	6	1400	965	218	670	319	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061400HA0FA	1.94	999999	999999	426	316	251	207	176	130	110
NAGP061400HA0FA	1.92	999999	999999	481	345	272	224	190	139	118
NAGP061400HA0FA	1.90	999999	999999	532	376	295	241	204	149	126
NAGP061400HA0FA	1.88	999999	999999	574	401	312	254	215	157	132
NAGP061400HA0FA	1.86	999999	999999	618	424	329	270	230	163	138
NAGP061400HA0FA	1.84	999999	999999	651	446	346	279	235	168	141
NAGP061400HA0FA	1.83	999999	999999	669	455	353	282	238	168	143
NAGP061400HA0FA	1.81	1115	926	696	470	363	288	244	170	144
NAGP061400HA0FA	1.80	1148	949	702	470	364	290	246	171	144
NAGP061400HA0FA	1.78	1219	984	715	483	367	294	247	172	145
NAGP061400HA0FA	1.75	1304	1041	728	496	369	298	251	175	146