


Absolyte – 3-100G31 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP061496 **H** A0FA

UL 94 V0 NAGP061496 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G31	6	1496	1022	218	670	340	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061496HA0FA	1.94	999999	999999	456	339	269	222	189	139	118
NAGP061496HA0FA	1.92	999999	999999	516	370	291	240	204	149	127
NAGP061496HA0FA	1.90	999999	999999	570	403	316	259	219	159	135
NAGP061496HA0FA	1.88	999999	999999	615	430	334	273	231	168	142
NAGP061496HA0FA	1.86	999999	999999	663	454	353	289	246	175	148
NAGP061496HA0FA	1.84	999999	999999	697	478	371	299	251	180	152
NAGP061496HA0FA	1.83	999999	999999	717	488	378	303	255	180	153
NAGP061496HA0FA	1.81	1195	993	746	503	389	308	261	182	154
NAGP061496HA0FA	1.80	1230	1017	753	504	390	311	263	183	155
NAGP061496HA0FA	1.78	1306	1054	766	518	393	315	265	184	155
NAGP061496HA0FA	1.75	1398	1116	780	532	396	320	269	187	156