


Absolyte – 3-100G33 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP061600 **H** A0FA
 UL 94 V0 NAGP061600 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
3-100G33	6	1600	1080	218	670	361	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP061600HA0FA	1.94	999999	999999	487	362	287	237	201	148	126
NAGP061600HA0FA	1.92	999999	999999	550	395	311	256	217	159	135
NAGP061600HA0FA	1.90	999999	999999	608	430	337	276	233	170	144
NAGP061600HA0FA	1.88	999999	999999	656	459	357	291	246	179	151
NAGP061600HA0FA	1.86	999999	999999	707	484	377	309	263	187	158
NAGP061600HA0FA	1.84	999999	999999	744	510	396	319	268	192	162
NAGP061600HA0FA	1.83	999999	999999	764	520	403	323	272	192	163
NAGP061600HA0FA	1.81	1275	1059	796	537	415	329	279	195	164
NAGP061600HA0FA	1.80	1312	1084	803	538	416	331	281	195	165
NAGP061600HA0FA	1.78	1393	1124	817	552	419	336	282	196	166
NAGP061600HA0FA	1.75	1491	1190	832	567	422	341	287	200	167