


Absolyte – 6-50G05 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120104 **H** A0FA
 UL 94 V0 NAGP120104 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-50G05	12	104	437	217	412	71.0	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120104HA0FA	1.94	999999	999999	37.0	24.0	20.0	16.0	14.0	9.00	8.00
NAGP120104HA0FA	1.92	999999	999999	41.0	28.0	21.0	17.0	15.0	10.0	8.00
NAGP120104HA0FA	1.90	999999	999999	44.0	29.0	23.0	18.0	16.0	11.0	9.00
NAGP120104HA0FA	1.88	999999	999999	47.0	31.0	23.0	19.0	16.0	11.0	9.00
NAGP120104HA0FA	1.86	999999	999999	50.0	33.0	24.0	20.0	17.0	12.0	10.0
NAGP120104HA0FA	1.84	999999	999999	52.0	34.0	25.0	20.0	17.0	12.0	10.0
NAGP120104HA0FA	1.83	999999	999999	53.0	34.0	26.0	20.0	17.0	12.0	10.0
NAGP120104HA0FA	1.81	118	86.0	54.0	35.0	26.0	21.0	18.0	12.0	10.0
NAGP120104HA0FA	1.80	120	88.0	55.0	36.0	27.0	21.0	18.0	12.0	10.0
NAGP120104HA0FA	1.78	126	91.0	57.0	36.0	27.0	22.0	18.0	12.0	10.0
NAGP120104HA0FA	1.75	133	94.0	58.0	37.0	27.0	22.0	18.0	13.0	11.0