


# Absolyte – 6-50G07 data sheet



Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

*Example*

Standard                    NAGP120152 **H** A0FA  
 UL 94 V0                    NAGP120152 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-50G07	12	152	551	217	412	95.0	F-M6

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120152HA0FA	1.94	999999	999999	56.0	36.0	30.0	24.0	21.0	14.0	12.0
NAGP120152HA0FA	1.92	999999	999999	62.0	42.0	32.0	26.0	22.0	15.0	13.0
NAGP120152HA0FA	1.90	999999	999999	67.0	44.0	34.0	28.0	24.0	16.0	14.0
NAGP120152HA0FA	1.88	999999	999999	70.0	47.0	35.0	29.0	24.0	17.0	14.0
NAGP120152HA0FA	1.86	999999	999999	75.0	49.0	37.0	30.0	25.0	18.0	15.0
NAGP120152HA0FA	1.84	999999	999999	78.0	51.0	38.0	31.0	26.0	18.0	15.0
NAGP120152HA0FA	1.83	999999	999999	80.0	52.0	39.0	31.0	26.0	18.0	15.0
NAGP120152HA0FA	1.81	177	129	82.0	53.0	40.0	32.0	27.0	19.0	15.0
NAGP120152HA0FA	1.80	181	132	83.0	54.0	40.0	32.0	27.0	19.0	16.0
NAGP120152HA0FA	1.78	189	136	85.0	55.0	41.0	33.0	27.0	19.0	16.0
NAGP120152HA0FA	1.75	199	142	87.0	56.0	41.0	33.0	28.0	19.0	16.0