


Absolyte – 6-50G09 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120208 **H** A0FA
 UL 94 V0 NAGP120208 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-50G09	12	208	665	217	412	114	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120208HA0FA	1.94	999999	999999	75.0	48.0	40.0	33.0	28.0	19.0	16.0
NAGP120208HA0FA	1.92	999999	999999	83.0	56.0	43.0	35.0	30.0	21.0	17.0
NAGP120208HA0FA	1.90	999999	999999	89.0	59.0	46.0	37.0	32.0	22.0	18.0
NAGP120208HA0FA	1.88	999999	999999	94.0	62.0	47.0	38.0	32.0	23.0	19.0
NAGP120208HA0FA	1.86	999999	999999	100	66.0	49.0	40.0	34.0	24.0	20.0
NAGP120208HA0FA	1.84	999999	999999	104	68.0	51.0	41.0	35.0	24.0	20.0
NAGP120208HA0FA	1.83	999999	999999	106	69.0	52.0	41.0	35.0	24.0	20.0
NAGP120208HA0FA	1.83	999999	999999	106	69.0	52.0	41.0	35.0	24.0	20.0
NAGP120208HA0FA	1.81	236	172	109	71.0	53.0	43.0	36.0	25.0	21.0
NAGP120208HA0FA	1.80	241	176	111	72.0	53.0	43.0	36.0	25.0	21.0
NAGP120208HA0FA	1.78	252	182	114	73.0	54.0	44.0	37.0	25.0	21.0
NAGP120208HA0FA	1.75	266	189	116	75.0	55.0	44.0	37.0	26.0	22.0