


Absolyte – 6-50G13 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120312 **H** A0FA
 UL 94 V0 NAGP120312 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-50G13	12	312	894	217	412	162	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120312HA0FA	1.94	999999	999999	112	73.0	60.0	49.0	42.0	29.0	25.0
NAGP120312HA0FA	1.92	999999	999999	125	84.0	64.0	53.0	45.0	31.0	26.0
NAGP120312HA0FA	1.90	999999	999999	134	89.0	69.0	56.0	48.0	33.0	28.0
NAGP120312HA0FA	1.88	999999	999999	141	94.0	71.0	58.0	49.0	34.0	29.0
NAGP120312HA0FA	1.86	999999	999999	150	99.0	74.0	61.0	51.0	36.0	30.0
NAGP120312HA0FA	1.84	999999	999999	156	102	77.0	62.0	52.0	36.0	30.0
NAGP120312HA0FA	1.83	999999	999999	160	104	78.0	62.0	53.0	37.0	31.0
NAGP120312HA0FA	1.81	354	259	164	106	80.0	64.0	54.0	38.0	31.0
NAGP120312HA0FA	1.80	362	264	167	108	80.0	65.0	54.0	38.0	32.0
NAGP120312HA0FA	1.78	378	273	171	110	82.0	66.0	55.0	38.0	32.0
NAGP120312HA0FA	1.75	399	284	175	112	83.0	67.0	56.0	39.0	33.0