


# Absolyte – 6-90G07 data sheet

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

*Example*

Standard                    NAGP120256 **H** A0FA  
 UL 94 V0                    NAGP120256 **V** A0FA

| Exide type designation | Nom. Voltage V | Nom. capacity C <sub>8</sub><br>1.75 Vpc 25°C<br>Ah | Length (l) max. mm | Width (b/w) max. mm | Height (h1) max. mm | Weight approx. kg | Terminal |
|------------------------|----------------|---|--------------------|---------------------|---------------------|-------------------|----------|
| 6-90G07                | 12             | 256   | 551                | 217                 | 599                 | 143               | F-M6     |

## Constant-current discharge in A @ 25 °C

| Part number     | Vpc  | 15 min | 30 min | 1 h  | 2 h  | 3 h  | 4 h  | 5 h  | 8 h  | 10 h |
|-----------------|------|--------|--------|------|------|------|------|------|------|------|
| NAGP120256HA0FA | 1.94 | 999999 | 999999 | 91.0 | 63.0 | 49.0 | 41.0 | 35.0 | 26.0 | 21.0 |
| NAGP120256HA0FA | 1.92 | 999999 | 999999 | 99.0 | 68.0 | 53.0 | 44.0 | 37.0 | 27.0 | 23.0 |
| NAGP120256HA0FA | 1.90 | 999999 | 999999 | 105  | 73.0 | 56.0 | 46.0 | 39.0 | 28.0 | 24.0 |
| NAGP120256HA0FA | 1.88 | 999999 | 999999 | 115  | 76.0 | 59.0 | 48.0 | 41.0 | 30.0 | 25.0 |
| NAGP120256HA0FA | 1.86 | 999999 | 999999 | 123  | 80.0 | 62.0 | 51.0 | 43.0 | 30.0 | 26.0 |
| NAGP120256HA0FA | 1.84 | 999999 | 999999 | 129  | 84.0 | 63.0 | 51.0 | 43.0 | 31.0 | 26.0 |
| NAGP120256HA0FA | 1.83 | 999999 | 999999 | 131  | 85.0 | 64.0 | 52.0 | 44.0 | 31.0 | 26.0 |
| NAGP120256HA0FA | 1.81 | 224    | 187    | 138  | 87.0 | 65.0 | 53.0 | 45.0 | 32.0 | 27.0 |
| NAGP120256HA0FA | 1.80 | 230    | 192    | 141  | 88.0 | 66.0 | 53.0 | 45.0 | 32.0 | 27.0 |
| NAGP120256HA0FA | 1.78 | 244    | 200    | 145  | 90.0 | 67.0 | 54.0 | 46.0 | 32.0 | 27.0 |
| NAGP120256HA0FA | 1.75 | 264    | 214    | 151  | 93.0 | 69.0 | 55.0 | 47.0 | 32.0 | 27.0 |