


Absolyte – 6-90G11 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120432 **H** A0FA
 UL 94 V0 NAGP120432 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-90G11	12	432	780	217	599	216	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120432HA0FA	1.94	999999	999999	151	105	82.0	69.0	58.0	43.0	36.0
NAGP120432HA0FA	1.92	999999	999999	165	114	88.0	74.0	63.0	45.0	38.0
NAGP120432HA0FA	1.90	999999	999999	175	123	94.0	78.0	66.0	47.0	40.0
NAGP120432HA0FA	1.88	999999	999999	192	127	99.0	81.0	68.0	50.0	42.0
NAGP120432HA0FA	1.86	999999	999999	205	134	103	86.0	72.0	51.0	43.0
NAGP120432HA0FA	1.84	999999	999999	215	140	106	86.0	73.0	51.0	44.0
NAGP120432HA0FA	1.84	999999	999999	215	140	106	86.0	73.0	51.0	44.0
NAGP120432HA0FA	1.83	999999	999999	219	142	108	88.0	74.0	52.0	44.0
NAGP120432HA0FA	1.81	373	312	230	145	109	89.0	76.0	53.0	45.0
NAGP120432HA0FA	1.80	384	321	236	147	110	88.0	76.0	53.0	45.0
NAGP120432HA0FA	1.78	408	334	242	151	112	91.0	77.0	54.0	45.0
NAGP120432HA0FA	1.75	441	357	251	155	115	93.0	78.0	54.0	46.0