


Absolyte – 6-90G13 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120520 **H** A0FA
 UL 94 V0 NAGP120520 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-90G13	12	520	894	217	599	253	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120520HA0FA	1.94	999999	999999	182	126	98.0	82.0	70.0	52.0	43.0
NAGP120520HA0FA	1.92	999999	999999	198	137	106	89.0	75.0	55.0	46.0
NAGP120520HA0FA	1.90	999999	999999	210	147	113	93.0	79.0	57.0	48.0
NAGP120520HA0FA	1.88	999999	999999	230	153	119	97.0	82.0	60.0	50.0
NAGP120520HA0FA	1.86	999999	999999	246	161	124	103	87.0	61.0	52.0
NAGP120520HA0FA	1.84	999999	999999	258	168	127	103	87.0	62.0	53.0
NAGP120520HA0FA	1.83	999999	999999	263	170	129	105	89.0	62.0	53.0
NAGP120520HA0FA	1.81	448	375	276	175	131	107	91.0	64.0	54.0
NAGP120520HA0FA	1.80	461	385	283	177	132	106	91.0	64.0	54.0
NAGP120520HA0FA	1.78	489	401	290	181	135	109	93.0	65.0	55.0
NAGP120520HA0FA	1.75	529	428	302	186	138	111	94.0	65.0	55.0