


Absolyte – 6-90G15 data sheet

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NAGP120608 **H** A0FA
 UL 94 V0 NAGP120608 **V** A0FA

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal
6-90G15	12	608	1008	218	599	289	F-M6

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGP120608HA0FA	1.94	999999	999999	212	147	115	96.0	81.0	60.0	50.0
NAGP120608HA0FA	1.92	999999	999999	231	160	124	103	88.0	64.0	54.0
NAGP120608HA0FA	1.90	999999	999999	245	172	132	109	93.0	67.0	56.0
NAGP120608HA0FA	1.88	999999	999999	269	178	138	113	96.0	70.0	58.0
NAGP120608HA0FA	1.86	999999	999999	287	188	144	120	101	71.0	61.0
NAGP120608HA0FA	1.84	999999	999999	301	196	148	120	102	72.0	62.0
NAGP120608HA0FA	1.83	999999	999999	307	199	151	123	104	72.0	62.0
NAGP120608HA0FA	1.81	522	437	322	204	153	125	106	74.0	63.0
NAGP120608HA0FA	1.80	538	449	331	206	154	124	107	75.0	63.0
NAGP120608HA0FA	1.78	571	468	338	212	157	127	109	76.0	64.0
NAGP120608HA0FA	1.75	618	499	352	217	162	130	110	76.0	64.0