


# Absolyte – GX2000 data sheet



No specific photo available

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal	Terminal alignment
GX2000	4	2000	967	543	291	315	F-M6	

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGX042000VA0FA	1.94			622	471	372	307	261	181	151
NAGX042000VA0FA	1.92			718	519	403	330	281	195	163
NAGX042000VA0FA	1.90			769	555	431	354	300	209	174
NAGX042000VA0FA	1.88			845	586	452	371	316	220	183
NAGX042000VA0FA	1.86			897	615	472	386	328	228	190
NAGX042000VA0FA	1.85			919	627	481	394	334	232	193
NAGX042000VA0FA	1.84			941	638	489	400	339	235	196
NAGX042000VA0FA	1.83			963	647	496	405	344	238	198
NAGX042000VA0FA	1.81			1003	666	508	414	351	243	202
NAGX042000VA0FA	1.80	1643	1399	1023	674	513	418	354	245	203
NAGX042000VA0FA	1.78	1758	1467	1060	687	521	423	358	247	206
NAGX042000VA0FA	1.75	1913	1569	1108	702	529	429	362	250	208
NAGX042000VA0FA	1.70	2157	1702	1167	716	536	433	366	253	210
NAGX042000VA0FA	1.60	2578	1907	1223	726	540	437	369	254	212
NAGX042000VA0FA	1.50	2938	2023	1241	729	542	438	369	255	212