


Absolyte – GX3000 data sheet



No specific photo available

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal	Terminal alignment
GX3000	4	3000	967	543	396	447	F-M6	

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGX043000VA0FA	1.94			934	706	558	460	391	271	226
NAGX043000VA0FA	1.92			1077	778	604	495	421	293	244
NAGX043000VA0FA	1.90			1153	832	647	530	451	313	261
NAGX043000VA0FA	1.88			1268	878	678	556	473	330	275
NAGX043000VA0FA	1.86			1346	923	709	580	492	342	285
NAGX043000VA0FA	1.85			1379	940	722	590	501	348	290
NAGX043000VA0FA	1.84			1412	957	734	599	509	353	294
NAGX043000VA0FA	1.83			1444	971	744	608	516	357	298
NAGX043000VA0FA	1.81			1505	999	762	622	527	364	303
NAGX043000VA0FA	1.80	2465	2099	1535	1011	770	627	531	367	305
NAGX043000VA0FA	1.78	2637	2200	1589	1031	781	635	537	371	308
NAGX043000VA0FA	1.75	2869	2353	1662	1053	793	643	544	375	312
NAGX043000VA0FA	1.70	3235	2553	1750	1074	803	650	549	379	315
NAGX043000VA0FA	1.60	3867	2861	1835	1089	810	655	553	382	318
NAGX043000VA0FA	1.50	4406	3034	1861	1094	812	656	554	383	318