


# Absolyte – GX4000 data sheet



No specific photo available

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal	Terminal alignment
GX4000	4	4000	967	543	582	630	F-M6	

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGX044000VA0FA	1.94			1245	942	744	613	522	362	301
NAGX044000VA0FA	1.92			1436	1037	806	661	562	391	326
NAGX044000VA0FA	1.90			1537	1109	862	707	601	418	348
NAGX044000VA0FA	1.88			1691	1171	905	742	631	439	367
NAGX044000VA0FA	1.86			1795	1230	945	773	656	456	380
NAGX044000VA0FA	1.85			1838	1253	963	787	669	464	387
NAGX044000VA0FA	1.84			1882	1276	978	799	678	470	392
NAGX044000VA0FA	1.83			1926	1295	992	811	688	477	397
NAGX044000VA0FA	1.81			2006	1331	1016	829	702	486	404
NAGX044000VA0FA	1.80	3286	2798	2046	1347	1026	836	708	489	407
NAGX044000VA0FA	1.78	3516	2934	2119	1374	1041	847	716	495	411
NAGX044000VA0FA	1.75	3826	3138	2216	1405	1058	858	725	500	416
NAGX044000VA0FA	1.70	4314	3404	2333	1432	1071	867	732	505	420
NAGX044000VA0FA	1.60	5156	3814	2447	1453	1081	873	737	509	424
NAGX044000VA0FA	1.50	5876	4046	2481	1458	1083	875	739	510	425