


# Absolyte – GX5000 data sheet



No specific photo available

Terminal: Drawing:



## Specifications:

Part numbers not valid for North America, use type for ordering!

Exide type designation	Nom. Voltage V	Nom. capacity C <sub>8</sub> 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal	Terminal alignment
GX5000	4	5000	967	543	687	762	F-M6	

## Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGX045000VA0FA	1.94			1556	1177	930	766	652	452	377
NAGX045000VA0FA	1.92			1795	1296	1007	826	702	488	407
NAGX045000VA0FA	1.90			1922	1387	1078	884	751	522	435
NAGX045000VA0FA	1.88			2113	1464	1131	927	789	549	458
NAGX045000VA0FA	1.86			2244	1538	1181	966	820	570	476
NAGX045000VA0FA	1.85			2298	1566	1203	984	836	580	484
NAGX045000VA0FA	1.84			2353	1595	1223	999	848	588	490
NAGX045000VA0FA	1.83			2407	1618	1240	1013	860	596	496
NAGX045000VA0FA	1.81			2508	1664	1270	1036	878	607	505
NAGX045000VA0FA	1.80	4108	3498	2558	1684	1283	1045	885	611	509
NAGX045000VA0FA	1.78	4395	3667	2649	1718	1302	1058	895	618	514
NAGX045000VA0FA	1.75	4782	3922	2770	1756	1322	1072	906	625	520
NAGX045000VA0FA	1.70	5392	4255	2917	1790	1339	1083	915	632	525
NAGX045000VA0FA	1.60	6445	4768	3059	1816	1351	1092	922	636	530
NAGX045000VA0FA	1.50	7344	5057	3101	1823	1354	1094	924	638	531