


Absolyte – GX6000 data sheet



No specific photo available

Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Exide type designation	Nom. Voltage V	Nom. capacity C ₈ 1.75 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Weight approx. kg	Terminal	Terminal alignment
GX6000	4	6000	967	543	792	894	F-M6	

Constant-current discharge in A @ 25 °C

Part number	Vpc	15 min	30 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h
NAGX046000VA0FA	1.94			1867	1413	1116	920	782	543	452
NAGX046000VA0FA	1.92			2154	1556	1208	991	843	586	489
NAGX046000VA0FA	1.90			2306	1664	1293	1061	901	626	522
NAGX046000VA0FA	1.88			2536	1757	1357	1113	947	659	550
NAGX046000VA0FA	1.86			2692	1845	1417	1159	985	684	571
NAGX046000VA0FA	1.85			2757	1880	1444	1181	1003	696	580
NAGX046000VA0FA	1.84			2823	1914	1467	1199	1017	706	588
NAGX046000VA0FA	1.83			2889	1942	1488	1216	1032	715	595
NAGX046000VA0FA	1.81			3010	1997	1525	1243	1053	729	606
NAGX046000VA0FA	1.80	4930	4198	3069	2021	1539	1254	1062	734	610
NAGX046000VA0FA	1.78	5274	4400	3179	2062	1562	1270	1074	742	617
NAGX046000VA0FA	1.75	5738	4706	3324	2107	1586	1286	1087	750	624
NAGX046000VA0FA	1.70	6470	5106	3500	2148	1607	1300	1098	758	630
NAGX046000VA0FA	1.60	7734	5722	3670	2179	1621	1310	1106	763	635
NAGX046000VA0FA	1.50	8812	6068	3722	2187	1625	1313	1108	765	637